

5L IATA Can

UN No: 1A1/X/250/**/GB/0478

A steel tight head drum manufactured in accordance with the UN packaging specification, and satisfies the provisions of the packaging and packaging waste directive 94/62/EC. Tested for Packaging Groups I, II, III.

Size:	5L
Closure:	G2 Tri-Sure Steel Closures
Closing Torque:	25N/m
Weight:	1.5kg
Overall Height (mm):	206
Diameter (mm):	207
Drop Height:	1.8m
Steel Plate Thickness (mm):	Top End: 1.0 +/- .05
	Body: 0.6 +/- .05
	Bottom: 1.0 +/- .05
Side Seam:	Welded
End Seams:	Double Seamed & Solutioned
Rolling Hoops:	None
Handle:	Wire Drop handle
Internal Finish:	Plain/ Epoxy Phenolic Lacquer
External Finish:	Stoving Enamel



Qty Per Pallet:	200
Pallet Size:	1100mm x 1100mm
Shrink Wrap:	Yes
Strap:	Optional
Pallet Hood:	Optional
Layer Pad:	Optional
Foam Wrap:	Optional

To test levels of	The packaging is approved as provided in the relevant transport rule, to contain liquids of		
Drop Height (m)	1.8	packaging group	density (d)
Leakproofness (kPa)	30	I	1.2
Stacked at 3m with RD(d)	1.2	II	1.2
Internal Pressure (kPa)	250	III	1.2

The facts given in this datasheet refer to the product status on the date of revision. Changes might occur on our own decision without additional customer information.

This data sheet is for reference only. Full specification can be provided on request. Values indicated may vary within permitted tolerances.
Suitability for purpose is subject to user verification.