

2.5L Jerrycan UN Freestanding

Weight (grammes):	130 +/- 2
Min. Wall thickness (mm):	0.54
Brimful capacity (ml):	2500
Neck details (mm):	Bore -31, Thread OD -37.3
Material:	HM-HDPE
Closures:	38mm & 38mm TE
Closing torque:	4-5Nm

Decoration

Label area:	2 panels of 125mm high x 85mm wide
Print:	2 panels of 127mm high x 76mm wide

Packing Configuration

Pack Type:	Bagged on Pallets , 40 per bag
Pallet size:	1000mm x 1200 x 1265mm high
No. per pallet:	400



Height (mm): 223

Width (mm): 148

Depth (mm): 107

All Nexus containers are manufactured in facilities registered to ISO9001:2000 Quality Management Systems and BRC/Iop technical standards for food packaging manufacturers (Category B).

These containers are suitable for food contact and meet the requirements of the Food Safety Act, Plastic Materials in Contact with Food regulations and all other applicable legislation, including global migration limits with model foods for 10 days up to 40 °C. Test reports and certificates are available on request.

They meet the requirements of the Packaging Essential Requirements regulations including the limits of heavy metal and noxious substances content. Test reports and certificates are available on request.

Nexus can assist with customers' legislative requirements and use a UKAS accredited laboratory for conducting UN dangerous goods carriage tests. Full details on request.

We offer full technical and practical advice on the use of our containers.

This product specification is for reference only. Values and dimensions shown may vary within permitted manufacturing tolerances.
SUITABILITY FOR PURPOSE IS SUBJECT TO USER VERIFICATION.