

4L Jerrycan

Weight (grammes):	110 and 130
Min. Wall thickness (mm):	0.50
Brimful capacity (ml):	4275 +/-80
Neck details (mm):	Bore -31, Thread OD -37.2
Material:	HDPE
Closures:	38mm & 38mm TE
Closing torque:	2.7Nm

Decoration

Label area:	2 panels of 145mm high x 97mm wide
Print:	2 panels of 140mm high x 95mm wide

Packing Configuration

Pack Type:	Pallet
Pallet size:	1024mm x 1328 x 2490mm high
No. per pallet:	2 pallets of 280
Lift quantity:	560



Height (mm): 260

Width (mm): 166

Depth (mm): 128

All Nexus containers are manufactured in facilities registered to ISO9001:2000 Quality Management Systems and BRC/Iop technical standards for food packaging manufacturers (Category B).

These containers are suitable for food contact and meet the requirements of the Food Safety Act, Plastic Materials in Contact with Food regulations and all other applicable legislation, including global migration limits with model foods for 10 days up to 40 °C. Test reports and certificates are available on request.

They meet the requirements of the Packaging Essential Requirements regulations including the limits of heavy metal and noxious substances content. Test reports and certificates are available on request.

Nexus can assist with customers' legislative requirements and use a UKAS accredited laboratory for conducting UN dangerous goods carriage tests. Full details on request.

We offer full technical and practical advice on the use of our containers.

This product specification is for reference only. Values and dimensions shown may vary within permitted manufacturing tolerances.
SUITABILITY FOR PURPOSE IS SUBJECT TO USER VERIFICATION.