

## 5L LX Jerrycan

<b>Weight (grammes):</b>	130 and 145 +/- 4.5
<b>Min. Wall thickness (mm):</b>	0.38
<b>Brimful capacity (ml):</b>	5000
<b>Neck details (mm):</b>	Bore -30.9, Thread OD -37.5
<b>Material:</b>	HDPE
<b>Closures:</b>	38mm
<b>Closing torque:</b>	3.2Nm

### Decoration

<b>Label area:</b>	2 panels of 150mm high x 115mm wide
<b>Print:</b>	150mm high x circumference

### Packing Configuration

<b>Pack Type:</b>	Palletised and stretch wrapped
<b>Pallet size:</b>	1100mm x 1100mm x 1278mm high - 4 High 1100mm x 1100mm x 1560mm high - 5 High
<b>No. per pallet:</b>	96 - 4 High, 112 - 5 High



**Height (mm):** 283

**Width (mm):** 185

**Depth (mm):** 135

All Nexus containers are manufactured in facilities registered to ISO9001:2000 Quality Management Systems and BRC/Iop technical standards for food packaging manufacturers (Category B).

These containers are suitable for food contact and meet the requirements of the Food Safety Act, Plastic Materials in Contact with Food regulations and all other applicable legislation, including global migration limits with model foods for 10 days up to 40 °C. Test reports and certificates are available on request.

They meet the requirements of the Packaging Essential Requirements regulations including the limits of heavy metal and noxious substances content. Test reports and certificates are available on request.

Nexus can assist with customers' legislative requirements and use a UKAS accredited laboratory for conducting UN dangerous goods carriage tests. Full details on request.

We offer full technical and practical advice on the use of our containers.

This product specification is for reference only. Values and dimensions shown may vary within permitted manufacturing tolerances. SUITABILITY FOR PURPOSE IS SUBJECT TO USER VERIFICATION.