

Jerrycan 5L UN Freestanding

Weight (grammes):	200
Min. Wall thickness (mm):	0.6
Brimful capacity (ml):	5000
Neck details (mm):	Bore -31.5, Thread OD -37.4
Material:	HDPE
Closures:	38mm & 38mm TE
Closing torque:	3.2Nm

Decoration

Label area:	2 panels of 175mm high x 102mm wide
Print:	2 panels of 152mm high x 102mm wide

Packing Configuration

Pack Type:	Trays and on pallet
Pallet size:	1072mm x 1293 x 861mm high
No. per pallet:	432



Height (mm): 282

Width (mm): 185

Depth (mm): 133

All Nexus containers are manufactured in facilities registered to ISO9001:2000 Quality Management Systems and BRC/Iop technical standards for food packaging manufacturers (Category B).

These containers are suitable for food contact and meet the requirements of the Food Safety Act, Plastic Materials in Contact with Food regulations and all other applicable legislation, including global migration limits with model foods for 10 days up to 40 °C. Test reports and certificates are available on request.

They meet the requirements of the Packaging Essential Requirements regulations including the limits of heavy metal and noxious substances content. Test reports and certificates are available on request.

Nexus can assist with customers' legislative requirements and use a UKAS accredited laboratory for conducting UN dangerous goods carriage tests. Full details on request.

We offer full technical and practical advice on the use of our containers.

This product specification is for reference only. Values and dimensions shown may vary within permitted manufacturing tolerances.
SUITABILITY FOR PURPOSE IS SUBJECT TO USER VERIFICATION.