SPECIFICATION

Image 5L

Weight (grammes): 160 & 180

Min. Wall thickness (mm): 0.6

Nominal capacity (ml): 5000

Neck details (mm): Bore -31, Thread OD - 37.6

Material: HDPE

Closures: 38mm

Closing torque: 3.2Nm

Decoration

Label area: 2 panels of 130mm high x 125mm wide

plus sloped section.



Packing Configuration

Pack Type: Palletised

Pallet size: 1200 x 1000 x 1350 (3 high), 1483 (4 high)

No. per pallet: 150 (3 high), 200 (4 high)

All Nexus containers are manufactured in facilities registered to ISO9001:2000 Quality Management Systems and BRC/lop technical standards for food packaging manufacturers (Category B).

These containers are suitable for food contact and meet the requirements of the Food Safety Act, Plastic Materials in Contact with Food regulations and all other applicable legislation, including global migration limits with model foods for 10 days up to 40 °C. Test reports and certificates are available on request.

They meet the requirements of the Packaging Essential Requirements regulations including the limits of heavy metal and noxious substances content. Test reports and certificates are available on request.

Nexus can assist with customers' legislative requirements and use a UKAS accredited laboratory for conducting UN dangerous goods carriage tests. Full details on request.

We offer full technical and practical advice on the use of our containers.

This product specification is for reference only. Values and dimensions shown may vary within permitted manufacturing tolerances.

SUITABILITY FOR PURPOSE IS SUBJECT TO USER VERIFICATION

