

SPECIFICATION SHEET

120L Open Top Drum

UN/1H2/X225/S/./D/BAM8632-M

Product Name:	Standard open top drum
Nominal Volume [L]:	120,00 / 127,00
Body Colour:	blue
Body Weight [kg]:	4,5 (/)
Raw Material:	HDPE - Polyethylen
Min. Wall Thickness [mm]:	2,5
Min. Compression Value [N]:	18000
Overall Height (mm):	800
Height (mm):	790
Diameter (mm):	496
Height Labeling Field (mm):	250
Min. Ppening (mm):	395
Flange Diameter (mm):	445
LID - CLCS 400	B1 - -- --x-- B2 - -- --x--
Pack Type:	Loose
Pallet size:	--
No. per pallet:	--



Lid:	Standard lid S-400 interstackable black, foamed PU-gasket, Clampingring from steel [n.s.]
Closure B1:	Without bung
Closure B2:	Without bung

	Max. Vapour Pressure at 50°C	Max. Vapour Pressure at 55°C	Density PG I	Density PG II	Density PG III
Solids:	--	--	1,85	2,00	2,00
Water:	--	--	--	--	--
Acetic Acid:	--	--	--	--	--
Wetting Solution:	--	--	--	--	--
White Spirit:	--	--	--	--	--
N-Butyl Acetate:	--	--	--	--	--
Nitric Acid 55%:	--	--	--	--	--

The facts given in this datasheet refer to the product status on the date of revision. Changes might occur on our own decision without additional customer information.

This data sheet is for reference only. Full specification can be provided on request. Values indicated may vary within permitted tolerances.
Suitability for purpose is subject to user verification.