

SPECIFICATION SHEET

60L Open Top Drum

UN1H2/X88/S/./D/BAM8631-..

Product Name:	Standard open top drum with sidehandles
Nominal Volume [L]:	60,00 / 63,00
Body Colour:	blue
Body Weight [kg]:	2,5 (/)
Raw Material:	HDPE - Polyethylen
Min. Wall Thickness [mm]:	2,0
Min. Compression Value [N]:	10000

Overall Height (mm):	625
Height (mm):	615
Diameter (mm):	398
Height Labeling Field (mm):	174
Min. Opening (mm):	322
Flange Diameter (mm):	370
LID - CLCS 400	B1 - -- --x--
	B2 - -- --x--

Pack Type:	Shrunked
Pallet size:	1000 mm x 1200 mm
No. per pallet:	36 per pallet (full load 936)



Lid:	Standard lid S-320 interstackable black, foamed PU-gasket, Clampingring from steel [n.s.]
-------------	---

Closure B1: Without bung

Closure B2: Without bung

	Max. Vapour Pressure at 50°C	Max. Vapour Pressure at 55°C	Density PG I	Density PG II	Density PG III
Solids:	--	--	1,40	1,40	1,40
Water:	--	--	--	--	--
Acetic Acid:	--	--	--	--	--
Wetting Solution:	--	--	--	--	--
White Spirit:	--	--	--	--	--
N-Butyl Acetate:	--	--	--	--	--
Nitric Acid 55%:	--	--	--	--	--

The facts given in this datasheet refer to the product status on the date of revision. Changes might occur on our own decision without additional customer information.

This data sheet is for reference only. Full specification can be provided on request. Values indicated may vary within permitted tolerances.
Suitability for purpose is subject to user verification.